



## Main Feature

1. Small size (28.3x28.3x25.5 in mm) produces a switching capacity up to 40A for high density P.C.Board mounting technique.
2. The contact form construction is 1a/1c
3. The Surge Resistance of BAM10 series is 10,000V
4. Sealing Construction (Free from dust and solder flux): BAM10 -S: Flow Solder Type.
5. The selection of plastic insulation material is designed for high temperature and provides better chemical solution performance.

## Application

Air Conditioning, Fridge, Washing Machine, etc Household Appliances

## Contact Rating

- Nominal Load(Resistive Load Cos  $\phi$  =1)  
Contact Capacity  
BAM10-D.....30A at 14VDC  
BAM10-DM.....40A at 14VDC
- Max. Allowable Current  
BAM10-D..... 30A  
BAM10-DM.....40A
- Max. Allowable Voltage  
BAM10-D/DM..... DC14V
- Max. Allowable Power Force  
BAM10-D.....420W  
BAM10-DM.....560W
- Contact Material..... Ag Alloy
- Contact Form..... SPDT&SPST

## Performance (at Initial Value)

- Contact Resistance.....  $\leq 50m\Omega$  at 6VDC/1A
- Operate Time.....10ms. Max
- Release Time..... 5ms. Max
- Dielectric Strength:  
Between Coil & Contact.....700VAC at 50/60 Hz  
for one minute  
Between Contacts.....700VAC at 50/60 Hz  
for one minute
- Surge Resistance.....10,000V (between Coil  
& Contact 1.2x50  $\mu$ s)

- Insulation Resistance.....100 Mega  $\Omega$  Min. at  
500VDC
- Max. On/Off Switching:  
Electrical.....30 Ops per minute  
Mechanical.....300 Ops per minute
- Temperature Range..... - 40~85°C
- Humidity Range.....45~85% RH
- Coil Temperature Rise..... 35°C Maximum
- Vibration:  
Endurance.....10 to 55 Hz dual  
amplitude width 1.5mm  
Error Operation.....10 to 55 Hz dual  
amplitude width 1.5mm
- Shock:  
Endurance..... 981m/s<sup>2</sup> Min  
Error Operation..... 98.1m/s<sup>2</sup> Min
- Life Expectancy:  
Electrical.....10<sup>5</sup> Operations at  
Rated Resistive  
load  
Mechanical.....10<sup>7</sup> Operations at  
No load condition
- Weight.....about 42g

## Safety Standard & Its File Number

申请中

## Coil Specification (at 20 °C)

Coil Sensitivity	Nominal Voltage (VDC)	Nominal Current (mA)	Coil Resistance ( $\Omega \pm 8\%$ )	Power Consumption (W)	Pull-In Voltage (VDC)	Drop-Out Voltage (VDC)	Maximum Allowable Voltage (VDC)
BAM10-D/DM	3	200	6	Abt. 1.6	75% Maximum	10% Minimum	130%
	5	119	16				
	6	100	23				
	9	66.7	51				
	12	50	90				
	24	25	360				
	48	12.5	1440				

## Ordering Information

BAM10	-	S	-	1	12	D	M		
									<b>Contact Form:</b>
									<b>Nil:</b> One form C
									<b>M:</b> One form A
									<b>B:</b> One form B
									<b>D:</b> Standard DC Coil
									<b>Coil Type:</b>
									<b>Coil Voltage:</b> 03:3V, 05:5V,06:6V,09:9V,12:12V,24:24V,48:48V,
									<b>Number of Pole:</b> 1:One Pole
									<b>Type of Sealing:</b> S:How Solder Type
									<b>Type:</b> BAM10

## Classification

Model	BAM10	
Coil Sensitivity	Standard DC Coil	
	1A	1C
Flow Solder Type	BAM10 -S-1□□DM	BAM10 -S-1□□D

## Dimension

