

Coil Specification (at 20 °C)

Coil Sensitivity	Nominal Voltage (VDC)	Nominal Current (mA)	Coil Resistance ($\Omega \pm 8\%$)	Power Consumption (W)	Pull-In Voltage (VDC)	Drop-Out Voltage (VDC)	Maximum Allowable Voltage (VDC)
BSA2-DM3 BSA2-DM5	5	108.7	46	Abt. 0.54	75% Maximum	10% Minimum	130%
	6	85.7	70				
	9	58.1	155				
	12	44.4	270				
	24	21.8	1100				
	48	11.2	4270				

Ordering Information

BSA2 - SS - 2 12 D M 3		
	Contact Weld Mode:	3: Spot Welding 5: Hinge Match
	Contact Form:	M: Two form A
	Coil Type:	D: Standard DC Coil
	Coil Voltage:	05: 5V, 06: 6V, 09: 9V, 12: 12V, 24: 24V, 48: 48V
	Number of Pole:	2: Two Pole
	Type of Sealing:	SS: How Solder Type
	Type:	BSA2

Classification

Model	BSA2
Coil Sensitivity	Standard DC Coil
	2A
Flow Solder Type	BSA2 -SS-2□□DM3 BSA2 -SS-2□□DM5

Dimension

